

Microsoft

AZ-400

Designing and Implementing Microsoft DevOps Solutions



For More Information – Visit link below:

<https://www.examsboost.com/>

Product Version

- ✓ Up to Date products, reliable and verified.
- ✓ Questions and Answers in PDF Format.

Latest Version: 45.0

Question: 1

HOTSPOT

How should you complete the code to initialize App Center in the mobile application? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection a worth one point.

```
MSAppCenter.start
```

```
( "{Your App Secret}",  
  withServices:  
)
```

[MSAnalytics.self,
[MSDistribute.self,
[MSPush.self,

MSAnalytics.self]
MSCrashes.self]
MSDistribute.self]

Answer:

```
MSAppCenter.start
```

```
( "{Your App Secret}",  
  withServices:  
)
```

[MSAnalytics.self,
[MSDistribute.self,
[MSPush.self,

MSAnalytics.self]
MSCrashes.self]
MSDistribute.self]

Explanation:

Scenario: Visual Studio App Center must be used to centralize the reporting of mobile application crashes and device types in use.

In order to use App Center, you need to opt in to the service(s) that you want to use, meaning by default no services are started and you will have to explicitly call each of them when starting the SDK.

Insert the following line to start the SDK in your app's AppDelegate class in the didFinishLaunchingWithOptions method.

```
MSAppCenter.start("{Your App Secret}", withServices: [MSAnalytics.self, MSCrashes.self])
```

Reference: <https://docs.microsoft.com/en-us/appcenter/sdk/getting-started/ios>

Question: 2

HOTSPOT

How should you configure the release retention policy for the investment planning depletions suite? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Required secrets:

Certificate
Personal access token
Shared Access Authorization token
Username and password

Storage location:

Azure Data Lake
Azure Key Vault
Azure Storage with HTTP access
Azure Storage with HTTPS access

Answer:

Required secrets:

Certificate
Personal access token
Shared Access Authorization token
Username and password

Storage location:

Azure Data Lake
Azure Key Vault
Azure Storage with HTTP access
Azure Storage with HTTPS access

Explanation:

Every request made against a storage service must be authorized, unless the request is for a blob or container resource that has been made available for public or signed access. One option for authorizing a request is by using Shared Key.

Scenario: The mobile applications must be able to call the share pricing service of the existing retirement fund management system. Until the system is upgraded, the service will only support basic authentication over HTTPS.

The investment planning applications suite will include one multi-tier web application and two iOS mobile application. One mobile application will be used by employees; the other will be used by customers.

Reference: <https://docs.microsoft.com/en-us/rest/api/storageservices/authorize-with-shared-key>

Question: 3

HOTSPOT

You need to configure a cloud service to store the secrets required by the mobile applications to call the share.

What should you include in the solution? To answer, select the appropriate options in the answer area»,

NOTE: Each correct selection is worth one point.

Required secrets:

<input type="checkbox"/> Certificate
<input type="checkbox"/> Personal access token
<input type="checkbox"/> Shared Access Authorization token
<input type="checkbox"/> Username and password

Storage location:

<input type="checkbox"/> Azure Data Lake
<input type="checkbox"/> Azure Key Vault
<input type="checkbox"/> Azure Storage with HTTP access
<input type="checkbox"/> Azure Storage with HTTPS access

Answer:

Required secrets:

<input type="checkbox"/> Certificate
<input type="checkbox"/> Personal access token
<input checked="" type="checkbox"/> Shared Access Authorization token
<input type="checkbox"/> Username and password

Storage location:

<input type="checkbox"/> Azure Data Lake
<input type="checkbox"/> Azure Key Vault
<input type="checkbox"/> Azure Storage with HTTP access
<input checked="" type="checkbox"/> Azure Storage with HTTPS access

Explanation:

Every request made against a storage service must be authorized, unless the request is for a blob or container resource that has been made available for public or signed access. One option for authorizing a request is by using Shared Key.

Scenario: The mobile applications must be able to call the share pricing service of the existing retirement fund management system. Until the system is upgraded, the service will only support basic authentication over HTTPS.

The investment planning applications suite will include one multi-tier web application and two iOS mobile application. One mobile application will be used by employees; the other will be used by customers.

Reference: <https://docs.microsoft.com/en-us/rest/api/storageservices/authorize-with-shared-key>

Question: 4

To resolve the current technical issue, what should you do to the Register-AzureRmAutomationDscNode command?

- A. Change the value of the ConfigurationMode parameter.
- B. Replace the Register-AzureRmAutomationDscNode cmdlet with Register-AzureRmAutomationScheduledRunbook
- C. Add the AllowModuleOverwrite parameter.
- D. Add the DefaultProfile parameter.

Answer: A

Explanation:

Change the ConfigurationMode parameter from ApplyOnly to ApplyAndAutocorrect.

The Register-AzureRmAutomationDscNode cmdlet registers an Azure virtual machine as an APS Desired State Configuration (DSC) node in an Azure Automation account.

Scenario: Current Technical Issue

The test servers are configured correctly when first deployed, but they experience configuration drift over time. Azure Automation State Configuration fails to correct the configurations.

Azure Automation State Configuration nodes are registered by using the following command.

```
Register-AzureRmAutomationDscNode
  -ResourceGroupName 'TestResourceGroup'
  -AutomationAccountName 'LitwareAutomationAccount'
  -AzureVMName $vmname
  -ConfigurationMode 'ApplyOnly'
```

Reference: <https://docs.microsoft.com/en-us/powershell/module/azurerm.automation/registerazurermautomationdscnode?view=azurerm-6.13.0>

Question: 5

What should you use to implement the code quality restriction on the release pipeline for the investment planning applications suite?

- A. a trigger
- B. a pre deployment approval
- C. a post-deployment approval
- D. a deployment gate

Answer: B

Thank You for Trying Our Product

For More Information – **Visit link below:**

<https://www.examsboost.com/>

15 USD Discount Coupon Code:

G74JA8UF

FEATURES

- ✓ **90 Days Free Updates**
- ✓ **Money Back Pass Guarantee**
- ✓ **Instant Download or Email Attachment**
- ✓ **24/7 Live Chat Support**
- ✓ **PDF file could be used at any Platform**
- ✓ **50,000 Happy Customer**



Visit us at <https://www.examsboost.com/test/az-400/>