

Boost up Your Certification Score

Cisco

500-230

Cisco Service Provider Routing Field Engineer Exam



For More Information – Visit link below:

<https://www.examsboost.com/>

Product Version

- ✓ Up to Date products, reliable and verified.
- ✓ Questions and Answers in PDF Format.

Question: 1

What is the default MP-BGP address-family on IOS-XR?

- A. IPv6 unicast
- B. There is no default address-family
- C. IPv4 unicast
- D. VPNv4

Answer: B

Question: 2

Which command removes a user from configuration mode but keeps the user connected to the router?

- A. clear line
- B. clear session
- C. clear commit
- D. clear config session

Answer: D

Question: 3

Which command is used to configure an interface that does not currently exist in the system?

- A. interface preconfigure
- B. preconfigure interface
- C. interface vrf preconfig
- D. controller preconfigure

Answer: A

Question: 4

What is the TRACE command?

- A. A packet tracer showing the path of a packet from ingress to egress in the router.
- B. The replacement for TraceRoute in IOS-XR.
- C. A form of always-on debugging available for a subset of commands.

- D. Exactly the same as the debug command, must be explicitly turned on.

Answer: C

Question: 5

One of your peers show <NO NEG> in the SHOW BGP VPNV4 UNICAST SUMMARY output
What is the cause of this?

- A. The label value ranges are mismatched.
- B. The peer has no prefixes with a Route-Target that the local router is importing.
- C. The BGP prefixes between the routers have not fully converged and will correct itself in time.
- D. The peer router is not configured to use the Vpnv4 address-family for this connection.

Answer: D

Thank You for Trying Our Product

For More Information – **Visit link below:**

<https://www.examsboost.com/>

15 USD Discount Coupon Code:

G74JA8UF

FEATURES

- ✓ **90 Days Free Updates**
- ✓ **Money Back Pass Guarantee**
- ✓ **Instant Download or Email Attachment**
- ✓ **24/7 Live Chat Support**
- ✓ **PDF file could be used at any Platform**
- ✓ **50,000 Happy Customer**

