Boost up Your Certification Score

Cisco

350-601

Implementing and Operating Cisco Data Center Core Technologies

For More Information – Visit link below:

https://www.examsboost.com/

Product Version

✓ Up to Date products, reliable and verified.
✓ Questions and Answers in PDF Format.

Visit us at: https://www.examsboost.com/test/350-601

Latest Version: 36.4

Question: 1

The Cisco UCS blade chassis must send SNMPv3 traps to a network monitoring system. The SNMP trap messages should be authenticated and have protection from closure. Which SNMP security privileged level should be configured?

A. noPriv
B. auth
C. noAuth
D. priv

Answer: D

Question: 2

What is the DHCP snooping bindings file shown here used for by the Cisco Nexus 9000 Series Switch?

```
3ebe1518
 TYPE DHCP-SNOOPING
 VERSION 1
 BEGIN
 1.1.1.1 512 0001.0001.0005 3EBE2881 Gi1/1 381e06dd02
 1.1.1.1 512 0001.0001.0002 3EBE2881 Gi1/1 01c1819c9f
 1.1.1.1 1536 0001.0001.0004 3EBE2881 Gi1/1 9ab3e4416e
 1.1.1.1 0484 0001.0001.0008 2EBE2281 Gi1/1 40032733f0
 1.1.1.1 1 0001.0001.0001 3EBE2881 Gi1/1 23cfc94db4
```

A. to retain the DHCP bindings configuration across reboots
B. to authenticate the users permitted to make the changes to the DHCP snooping feature
C. to retain the DHCP server configuration across rebootsD, to permit the users from the IP addresses listed to make changes to the DCHP configuration

Answer: A

Question: 3

A network architect considers a Cisco HyperFlex design
solution for a company. The proposed solution is for a virtual environment that is not performance-sensitive, but the solution must have high storage capacity and a low cost. Which Cisco HyperFlex storage configuration should be used?

A. All-Flash
B. Hybrid
C. All-SAN
D. All-NVMe

Answer: B

Question: 4

What is a benefit of using the Cisco UCS Lightweight upgrade feature?

A. The firmware version of a component e updated only when it has boon modified.
B. A sod reboot is available for the fabric interconnects
C. Security updates are scheduled with the next reboot d the fabric interconnects.
D. All servers are rebooted to push the latest updates.

Answer: A

Question: 5

Refer to the exhibit.



Refer to the exhibit. Users report SAN traffic packet loss on a blade server that is managed by using Cisco UCS Manager. An engineer must implement a SPAN feature to an external Fibre Channel analyzer. Which configuration source in the TEST monitoring session must the engineer select?

A. all the storage ports
B. all the virtual host bus adapters from the server
C. all the uplink Fibre Channel ports
D. all the VSANs from the server

Answer: C

Thank You for Trying Our Product

For More Information – Visit link below:

https://www.examsboost.com/

15 USD Discount Coupon Code:

G74JA8UF

FEATURES

- ✓ 90 Days Free Updates
- ✓ Money Back Pass Guarantee
- ✓ Instant Download or Email Attachment
- ✓ 24/7 Live Chat Support
- ✓ PDF file could be used at any Platform
- ✓ 50,000 Happy Customer