

**Boost up Your Certification Score**

# **Fortinet NSE6\_FAZ-7.2**

**Fortinet NSE 6 - FortiAnalyzer 7.2 Administrator**



**For More Information – Visit link below:**

**<https://www.examsboost.com/>**

## **Product Version**

- ✓ Up to Date products, reliable and verified.
- ✓ Questions and Answers in PDF Format.

Visit us at: <https://www.examsboost.com/test/nse6-faz-7-2>

# Latest Version: 6.0

## Question: 1

Refer to the exhibit.

The screenshot shows the 'Cluster Settings' configuration page for a FortiAnalyzer. The 'Operation Mode' is set to 'High Availability' and the 'Preferred Role' is 'Primary'. The 'Cluster Virtual IP' is configured with IP Address '192.168.101.222' and Interface 'port1'. The 'Peer IP and Peer SN' section shows a peer with IP '10.0.1.210' and SN 'FAZ-VM0000065040'. The 'Group Name' is 'NSE6', 'Group ID' is '1', and the 'Password' is masked. The 'Heart Beat Interval' is '10' seconds, 'Failover Threshold' is '30', and 'Priority' is '120'. A toggle switch at the bottom is turned off.

Operation Mode	Standalone <b>High Availability</b>	
Preferred Role	Secondary <b>Primary</b>	
Cluster Virtual IP		
IP Address and Interface	IP Address: 192.168.101.222	Interface: port1
Cluster Settings		
Peer IP and Peer SN	Peer IP: 10.0.1.210	Peer SN: FAZ-VM0000065040
Group Name	NSE6	
Group ID	1	(1-255)
Password	*****	
Heart Beat Interval	10	Seconds
Failover Threshold	30	
Priority	120	

The image displays "he configuration of a FortiAnalyzer the administrator wants to join to an existing HA cluster.

What can you conclude from the configuration displayed?

- A. After joining to the cluster, this FortiAnalyzer will keep an updated log database.
- B. This FortiAnalyzer will trigger a failover after losing communication with its peers for 10 seconds.
- C. This FortiAnalyzer will join to the existing HA cluster as the primary.
- D. This FortiAnalyzer is configured to receive logs in its port1.

**Answer: D**

Explanation:

The configuration displayed in the exhibit indicates that the FortiAnalyzer is set up with a cluster virtual IP address of 192.168.101.222 assigned to interface port1. This setup is typically used for the FortiAnalyzer to receive logs on that interface when operating in a High Availability (HA) configuration. The exhibit does not provide enough information to conclude whether this FortiAnalyzer will be the primary unit in the HA cluster or the duration for the failover trigger; it only confirms the interface configuration for log reception. Reference: Based on the FortiAnalyzer 7.4.1 Administration Guide, the

similar configurations for HA and log reception are discussed, which would be relevant for understanding the settings in FortiAnalyzer 7.2.

# Thank You for Trying Our Product

For More Information – **Visit link below:**

**<https://www.examsboost.com/>**

15 USD Discount Coupon Code:

**G74JA8UF**

## FEATURES

- ✓ **90 Days Free Updates**
- ✓ **Money Back Pass Guarantee**
- ✓ **Instant Download or Email Attachment**
- ✓ **24/7 Live Chat Support**
- ✓ **PDF file could be used at any Platform**
- ✓ **50,000 Happy Customer**



Visit us at: <https://www.examsboost.com/test/nse6-faz-7-2>