

Fortinet

NSE7_OT-7.2

Fortinet NSE 7 - OT Security 7.2



For More Information – Visit link below:

<https://www.examsboost.com/>

Product Version

- ✓ Up to Date products, reliable and verified.
- ✓ Questions and Answers in PDF Format.

Latest Version: 11.2

Question: 1

Operational technology (OT) network analysts run different levels of reports to identify failures that could put the network at risk. Some of these reports may be related to device performance. Which FortiSIEM reporting method helps identify device failures?

- A. Device inventory reports
- B. Payment card industry (PCI) logging reports
- C. Configuration management database (CMDB) operational reports
- D. Business service reports

Answer: C

Question: 2

Which three methods of communication are used by FortiNAC to gather visibility information? (Choose three.)

- A. SNMP
- B. ICMP
- C. API
- D. RADIUS
- E. TACACS

Answer: A,C,D

Question: 3

Refer to the exhibit.

Edit SubPattern

Name:

Filters:

Paren	Attribute	Operator	Value
⊕ ⊖	Destination TCP/UDP Port	IN	Group: OT Ports
⊕ ⊖	Source TCP/UDP Port	IN	Group: OT Ports

Aggregate:

Paren	Attribute	Operator	Value
⊕ ⊖	COUNT(Matched Events)	>=	1

Group By:

Attribute	Row	Move
Reporting IP	⊕ ⊖	↑ ↓
Event Type	⊕ ⊖	↑ ↓
Destination TCP/UDP Port	⊕ ⊖	↑ ↓
Source TCP/UDP Port	⊕ ⊖	↑ ↓

An operational technology rule is created and successfully activated to monitor the Modbus protocol on FortiSIEM. However, the rule does not trigger incidents despite Modbus traffic and application logs being received correctly by FortiSIEM.

Which statement correctly describes the issue on the rule configuration?

- A. The first condition on the SubPattern filter must use the OR logical operator.
- B. The attributes in the Group By section must match the ones in Filters section.
- C. The Aggregate attribute COUNT expression is incompatible with the filters.
- D. The SubPattern is missing the filter to match the Modbus protocol.

Answer: B

Question: 4

What can be assigned using network access control policies?

- A. Layer 3 polling intervals
- B. FortiNAC device polling methods
- C. Logical networks
- D. Profiling rules

Answer: C

Question: 5

A FortiGate device is newly deployed as the edge gateway of an OT network security fabric. The downstream FortiGate devices are also newly deployed as Security Fabric leafs to protect the control area zone.

With no additional essential networking devices, and to implement micro-segmentation on this OT network, what configuration must the OT network architect apply to control intra-VLAN traffic?

- A. Enable transparent mode on the edge FortiGate device.
- B. Enable security profiles on all interfaces connected in the control area zone.
- C. Set up VPN tunnels between downstream and edge FortiGate devices.
- D. Create a software switch on each downstream FortiGate device.

Answer: D

Thank You for Trying Our Product

For More Information – **Visit link below:**

<https://www.examsboost.com/>

15 USD Discount Coupon Code:

G74JA8UF

FEATURES

- ✓ **90 Days Free Updates**
- ✓ **Money Back Pass Guarantee**
- ✓ **Instant Download or Email Attachment**
- ✓ **24/7 Live Chat Support**
- ✓ **PDF file could be used at any Platform**
- ✓ **50,000 Happy Customer**



Visit us at: <https://www.examsboost.com/test/nse7-ots-7-2>