Boost up Your Certification Score

Juniper

JN0-460

Mist AI Wired, Specialist

For More Information – Visit link below:

https://www.examsboost.com/

Product Version

✓ Up to Date products, reliable and verified.
✓ Questions and Answers in PDF Format.

Visit us at: https://www.examsboost.com/test/jn0-460

Latest Version: 10.1

Question: 1

Which statement is correct about a 3-stage campus fabric IP Clos?

A. The distribution layer is connected to the access layer.
B. The distribution layer is connected to the core layer.
C. The core layer is connected to the access layer.
D. The core layer devices are connected to each other.

Answer: C

Explanation:
Juniper's official Campus Fabric IP Clos designfor Mist Wired Assurance defines that the3-stage IP Closstopology eliminates the traditionaldistribution layerentirely. This architecture is intended for smaller campus environments that do not need an intermediate distribution layer between the access and core.
"Juniper's Wired Assurance supports 3-Stage and 5-Stage IP Clos deployments. The 3-Stage IP Clos is targeted towards deployments that do not require a Distribution Layer and have smaller scale requirements."
Because the distribution layer is not present, the only hierarchical connection in a 3-stage campus fabric is between thecore and access layers. Traffic is routed directly at the access layer, and each access switch acts as a Layer-3 gateway (IRB) for its VLANs.
"In a campus fabric IP Clos architecture, Mist provisions Layer-3 (L3) integrated routing and bridging (IRB) interfaces on the access layer. All the access switches are configured with the same IP address for each L3 subnet."
Additionally, the Juniper documentation explains that point-to-point links are configuredbetween layers, and in the case of the 3-stage design (with no distribution), this means between thecore and accessdevices:
"The point-to-point links between each layer utilize /31 addressing to conserve addresses."
Therefore, the correct statement isC: The core layer is connected to the access layer.
OptionsAandBincorrectly mention a distribution layer that does not exist in this topology.
OptionDis incorrect because core (spine) devices in a Clos fabric are not interconnected with each other.
Juniper Mist AI for Wired – Campus Fabric IP Clos Architecture Guide
Juniper Mist AI for Wired – Campus Fabric IP Clos Workflow
Juniper Mist AI for Wired – Configure Campus Fabric IP Clos
Juniper Validated Design – Campus Fabric IP Clos Deployment Types

Question: 2

Which three steps should be part of the campus fabric deployment?(Choose three.)

A. Define the physical connections.
B. Define the networks of interest.
C. Configure the DNS server.
D. Choose the topology.
E. Configure the group-based policy (GBP) tag.

Answer: A, B, D

Explanation:
According to theJuniper Mist AI for Wired – Campus Fabric IP Clos Deployment Workflow, deploying a campus fabric involves a defined sequence of planning and configuration steps within the Mist Cloud interface. The key stages include:
“To deploy a campus fabric, you must first define the topology type, identify the physical connections between devices, and define the networks of interest that will be extended across the fabric.”
Breaking this down:
Choose the topology (D):Selecting the correct fabric type (3-Stage or 5-Stage IP Clos) determines how access, distribution, and core switches will interconnect.
Define the physical connections (A):This step involves specifying the uplink and downlink relationships between switches so that Mist can auto-generate EVPN-VXLAN and routing configurations.
Define the networks of interest (B):These are the VLANs and subnets that need to be extended across the fabric for user and device connectivity.
Steps such asconfiguring DNS serversordefining GBP tagsarenot part of the campus fabric deployment workflowin Mist Wired; they are optional or separate configurations outside the main deployment flow.
Juniper Mist AI for Wired – Campus Fabric IP Clos Deployment Workflow
Juniper Mist AI for Wired – Configure Campus Fabric IP Clos
Juniper Validated Design – Campus Fabric Overview
==========

Question: 3

What is the primary benefit of using switch configuration templates?

A. They improve the performance of switches.
B. They reduce Junos OS upgrade times.
C. They make it easier to make switch-specific configuration changes.
D. They provide a consistent configuration for all switches in an organization.

Answer: D

Explanation:
InJuniper Mist AI for Wired, configuration templates are a foundational part ofswitch onboarding and management. The primary purpose of these templates is to ensure configuration consistency across all switches that belong to a specific site or organization.
“Switch configuration templates allow administrators to define a standard configuration that is automatically applied to all switches within a site or organization, ensuring consistency and reducing configuration errors.”
Templates can contain base configuration parameters such as NTP, syslog, VLANs, port profiles, and authentication settings. When new switches are onboarded to the Mist Cloud, they automatically inherit the template’s configuration, ensuring uniform behavior across the network fabric.
Option Ais incorrect — templates do not directly impact hardware performance.
Option Bis incorrect — templates are not related to upgrade times.
Option Cis incorrect — templates are used for uniformity, not for switch-specific changes.
Option Dcorrectly describes their main benefit —ensuring consistent configuration across all switches.
Juniper Mist AI for Wired – Switch Configuration Templates Guide
Juniper Mist AI for Wired – Wired Assurance Administration Guide
Juniper Validated Design – Mist Wired Configuration Best Practices

Question: 4

Referring to the exhibit, what is the purpose of theSavebutton in the upper-right corner of the Mist dashboard?

A. It generates a backup of the current port configuration.
B. It resets the port configuration to its default settings.
C. It previews the impact of the port configuration changes before applying them.
D. It applies the port configuration changes to the switch.

Answer: D

Explanation:
In theJuniper Mist AI for Wired dashboard, administrators can select one or more switch ports (as shown in the exhibit, e.g., port ge-0/0/25 on an EX4100-48MP). Once configuration changes

are made — such as VLAN assignment, port profiles, PoE settings, or administrative state — theSave buttonmust be clicked to confirm and apply those changes to the device.
“When making configuration changes in the Mist switch interface, the Save button must be used to confirm the modifications. Clicking Save applies the selected port settings to the switch through Mist Cloud.”
Option Ais incorrect: saving does not create a backup. Backups and snapshots are handled through Mist’s configuration archive, not via the Save button.
Option Bis incorrect: Save does not reset configuration; instead, it commits changes.
Option Cis incorrect: there is no preview function tied to Save.
Option Dis correct: the Save button is explicitly forapplying configuration changesto the selected switch or port(s).
Juniper Mist AI for Wired – Switch Port Configuration Guide
Juniper Mist AI for Wired – Wired Assurance Administration Guide
Juniper Mist Documentation – Managing Switch Interfaces

Question: 5

You have two sites connected to an EVPN network. Each site is using the172.16.1.0/24network for its own respective site.
How does EVPN prevent overlap in this scenario?

A. It elects a designated forwarder.
B. It uses a Layer 2 gateway.
C. It uses a route distinguisher.
D. It uses an Ethernet segment identifier (ESI).

Answer: C

Explanation:
EVPN, when used with VXLAN, leveragesBGP MPLS/VXLAN control plane mechanisms. To prevent overlapping IP prefixes between different tenants or sites, EVPN uses aRoute Distinguisher (RD).
“In EVPN-VXLAN, the route distinguisher (RD) makes routes unique when overlapping IP prefixes or MAC addresses are advertised between multiple tenants or sites.”
Option A(designated forwarder) applies to multi-homing in EVPN, not prefix uniqueness.
Option B(Layer 2 gateway) does not prevent IP overlap; it bridges VLANs.
Option D(ESI) is used for identifying multi-homed Ethernet segments, not to differentiate overlapping subnets.
Option C(Route Distinguisher) is correct, as it uniquely identifies routes even if the IP addresses are the same across sites.
Juniper Mist AI for Wired – EVPN-VXLAN Overview
Juniper Validated Design – EVPN-VXLAN Fundamentals
Junos OS EVPN Configuration Guide
==========

Thank You for Trying Our Product

For More Information – Visit link below:

https://www.examsboost.com/

15 USD Discount Coupon Code:

G74JA8UF

FEATURES

- ✓ 90 Days Free Updates
- ✓ Money Back Pass Guarantee
- ✓ Instant Download or Email Attachment
- ✓ 24/7 Live Chat Support
- ✓ PDF file could be used at any Platform
- ✓ 50,000 Happy Customer