HPE6-A89 HPE Networking Comware



For More Information - Visit link below:

https://www.examsboost.com/

Product Version

- ✓ Up to Date products, reliable and verified.
 - ✓ Questions and Answers in PDF Format.

Latest Version: 6.0

Question: 1

Which command creates VLAN 100 on a Comware switch? Response:

- A. vlan 100
- B. create vlan 100
- C. vlan batch 100
- D. set vlan 100

Answer: C

Question: 2

What happens if no ACL rule matches a packet and there is no default permit statement? Response:

- A. The packet is forwarded
- B. The packet is denied
- C. The packet is logged and dropped
- D. The packet is forwarded to the control plane

Answer: B

Question: 3

Scenario: A network has three interconnected Comware switches. The administrator notices redundant links but wants to prevent loops while still maintaining redundancy.

Which feature should be enabled to achieve this?

Response:

- A. Port Aggregation
- B. Loopback Detection
- C. Spanning Tree Protocol
- D. Broadcast Suppression

Answer: C

Question: 4

Which version of IGMP is required for source-specific multicast (SSM)? Response:

- A. IGMPv1
- B. IGMPv2
- C. IGMPv3
- D. IGMP-Snooping

Answer: C

Question: 5

How are member switches identified within an IRF fabric? Response:

- A. By VLAN ID
- B. By MAC address
- C. By IRF member ID
- D. By switch name

Answer: C

Question: 6

What is the function of the PVID on a trunk port? Response:

- A. Assigns default IP address
- B. Determines the VLAN for untagged frames
- C. Blocks tagged VLANs
- D. Enables STP on the VLAN

Answer: B

Question: 7

What is the function of a Designated Port in STP? Response:

- A. Provides a backup path
- B. Learns but does not forward frames
- C. Forwards frames toward the root bridge
- D. Forwards frames away from the segment

Answer: D

Question: 8

What is the primary purpose of using multiple OSPF areas? Response:

- A. To reduce the size of the routing table and improve scalability
- B. To increase packet forwarding speed
- C. To allow static routes to take priority over dynamic routes
- D. To enable NAT for internal networks

Answer: A

Question: 9

In BGP, what is the primary purpose of the AS-PATH attribute? Response:

- A. Determines interface cost
- B. Identifies loop-free routing
- C. Assigns route priority based on bandwidth
- D. Determines OSPF area

Answer: B

Question: 10

Which protocol should be used to securely manage a Comware switch over the network? Response:

- A. Telnet
- B. FTP
- C. SSH
- D. TFTP

Answer: C

Thank You for Trying Our Product

For More Information – Visit link below:

https://www.examsboost.com/

15 USD Discount Coupon Code:

G74JA8UF

FEATURES

- ✓ 90 Days Free Updates
- **✓** Money Back Pass Guarantee
- ✓ Instant Download or Email Attachment
- ✓ 24/7 Live Chat Support
- **✓** PDF file could be used at any Platform
- ✓ 50,000 Happy Customer

